

Link do produktu: <https://skleprower.pl/rower-mondraker-superfoxy-r-29-2023-sram-1x12-hlins-p-600.html>



ROWER MONDRAKER SUPERFOXY R 29 2023 SRAM 1x12 Öhlins

Cena	15 999,00 zł
Cena poprzednia	24 799,00 zł
Dostępność	Dostępny
Czas wysyłki	3 dni
Producent	MONDRAKER
Rozmiar ramy	S (38cm), M (42cm), L (47cm), XL (51cm)
Kolekcja	2023

Opis produktu

Jeśli szukasz super enduro od Mondraker ze wszystkim, czego będziesz potrzebować, aby zaatakować, gdy szlak prowadzi w dół, ale rama z włókna węglowego po prostu nie znajduje się na Twojej liście priorytetów, SUPERFOXY R jest dla Ciebie. Ma wszystkie wyselekcjonowane komponenty, począwszy od przedniego i tylnego zawieszenia Öhlins, najlepsze komponenty ONOFF, koła e*thirteen LG1 Plus Enduro... a co najważniejsze, spektakularną ramę wykonaną z naszego najwyższej klasy aluminium : STOP STEALTH. Spektakularne wzornictwo, piękne kolory i wszystko zaprojektowane tak, aby maksymalnie wykorzystać możliwości teraz już nic Cię nie powstrzyma.


RAMA	SuperFoxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 160mm travel, Forward Geometry, one piece Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, Max. capacity sealed bearings, ISCG 05
DAMPER	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings
WIDELEC	Öhlins RXF 38 M.2 29, 170mm,TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
STERY	ONOFF Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
MOSTEK KIEROWNICA	ONOFF Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore ONOFF Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
CHWYTY SZTYCA	Onoff Twin, 1lock-on, 135mm ONOFF Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm
SIODEŁKO HAMULCE	SDG BEL-AIR 3.0, LPU foam, steel rails KLAMKA: Sram DB8, tool reach adjust ZACISK: Sram DB8, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
KOŁA	OBRĘCZ: e*thirteen LG1 Enduro, IW30 Hookless, 6069 Welded Aluminum, 30mm internal width, tubeless ready, 28 spokes SZPRYCHY: e*thirteen custom Hive triple-butted black steel, alloy nipples, nipple washers PIASTA PRZÓD: e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts / PIASTA TYŁ: e*thirteen Superboost 12x157mm, triple-sealed, fully machined

OPONA	aluminum w/6-degree engagement, IS 6 bolts, Shimano freehub PRZÓD: Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead / TYŁ: Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
MECHANIZM KORBOWY	Truvativ Descendant 7K Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm, 32T, CNC-machined alloy, X-SYNC 2
SUPPORT ŁAŃCUCH TYLNA PRZERZUTKA	SRAM DUB BSA, sealed bearings, 73mm SRAM SX Eagle, 12s, Powerlock SRAM NX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
MANETKA KASETA WAGA	SRAM Trigger SX Eagle, 12s, X-Actuation 1:1 SRAM XG-1230, 11-50T, 12s 17.1 kg

Produkt posiada dodatkowe opcje:

Rozmiar ramy: S (38cm) , M (42cm) , L (47cm) , XL (51cm)

Geometria



	FRAME SIZE	S	M	L	XL
A	Seattube length	380 mm	420 mm	470 mm	510 mm
B	Toptube length	605 mm	625 mm	650 mm	670 mm
C	Bottom bracket drop	-20 mm	-20 mm	-20 mm	-20 mm
D	Bottom bracket height	350 mm	350 mm	350 mm	350 mm
E	Chainstay length	445 mm	445 mm	445 mm	445 mm
F	Seat tube angle	71°	71°	71°	71°
G	Effective seattube angle	76°	76°	76°	76°
H	Headtube angle	65°	65°	65°	65°
I	Fork Offset	44 mm	44 mm	44 mm	44 mm
J	Wheelbase	1224 mm	1245 mm	1273 mm	1293 mm
K	Headtube length	100 mm	110mm	130 mm	130 mm
L	Reach	450 mm	470 mm	490 mm	510 mm
M	Stack	621 mm	621 mm	639 mm	639 mm

